



# 插装阀用线圈

Coil for cartridge valve

## BYC06-19A-01G

**DC 24V**  
**AC 220V**

其它规格可定做  
Other can be customized



技术参数 /technical parameter




|                                  |    |          |                           |   |         |
|----------------------------------|----|----------|---------------------------|---|---------|
| 环境温度 Ambienttemperature          | °C | -25 ~ 50 | 防护等级 Degree of protection |   | IP65    |
| 电压波动范围 Voltage fluctuation range | %  | 85 ~ 110 | 通电持续率 Power on duration   | % | 100     |
| 额定功率 Rated power                 | W  | 22       | 绝缘等级 Insulation class     |   | H (180) |

## BYC06-22-01D

比例型  
proportional type

**DC 12V**  
**DC 24V**

其它规格可定做  
Other can be customized



技术参数 /technical parameter

|                                  |    |          |                           |   |         |
|----------------------------------|----|----------|---------------------------|---|---------|
| 环境温度 Ambienttemperature          | °C | -25 ~ 50 | 防护等级 Degree of protection |   | IP67    |
| 电压波动范围 Voltage fluctuation range | %  | 85 ~ 110 | 通电持续率 Power on duration   | % | 100     |
| 额定功率 Rated power                 | W  | 20       | 绝缘等级 Insulation class     |   | H (180) |

样本数据来源于试验室环境，仅供参考，贵公司如需最新数据或有特殊需求，欢迎联系博业液压工程师。  
The sample data comes from the laboratory environment and is only for reference. If your company needs the latest data or has special needs, please contact Boye hydraulic engineer.